

## **DIVISION 10 – SPECIALITIES**

### **SECTION 10155 - TOILET COMPARTMENTS**

#### **PART 1 - GENERAL**

##### 1.01 SUMMARY

- A. Provide toilet partitions and screens.

##### 1.02 SUBMITTALS

- A. Submit for approval samples, shop drawings, product data.

##### 1.03 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.

#### **PART 2 - PRODUCTS**

##### 2.01 MATERIALS

- A. Manufacturers: Accurate Partitions, Bobrick Washroom Equipment, General Partitions, Knickerbocker, Santana Products, Sanymetal or approved equal.
- B. Toilet Compartment Type and Mounting:
  - 1. Compartments: Ceiling-hung.
- C. Toilet Compartment Materials:
  - 1. Metal Toilet Compartments with Baked Enamel Finish: ASTM A 591, Class C, galvanized bonderized steel with baked enamel finish.

#### **PART 3 - EXECUTION**

### 3.01 INSTALLATION

- A. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance. Coordinate with work of other sections.
- B. Limit openings between panels, doors and pilasters to less than 1/2".
- C. Adjust hardware, clean, and protect work.

\*\*\*\*\* END OF SECTION 10155 – TOILET  
COMPARTMENTS \*\*\*\*\*

## **SECTION 10500 - METAL LOCKERS**

### **PART 1 - GENERAL**

#### 1.01 SUMMARY

- A. Provide metal lockers.

#### 1.02 SUBMITTALS

- A. Submit for approval samples, shop drawings, product data.

#### 1.03 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.

### **PART 2 - PRODUCTS**

#### 2.01 MATERIALS

- A. Manufacturers: Lyon Metal Products, Penco Products, Republic Storage Systems or approved equal.

B. Lockers: (5 required)

1. Type: Wardrobe lockers, sheet steel, 24 gage (.0239 inch) back and sides, 16 gage (.0598 inch) top, bottom, and doors.
2. Tier: Single-tier lockers - 15" W X 24" D X 72" H.
3. Face: Solid with punched louvers.
4. Locking: Padlock type.
5. Tops: Sloped.
6. Mounting: Elevated base.

**PART 3 - EXECUTION**

3.01 INSTALLATION

- A. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance. Coordinate with work of other sections.
- B. Restore damaged finishes and test for proper operation. Clean and protect work from damage.

\*\*\*\*\* END OF SECTION 10500 – METAL LOCKERS \*\*\*\*\*

**SECTION 10522 - FIRE EXTINGUISHERS AND WALL BRACKETS**

**PART 1 - GENERAL**

1.01 SUMMARY

A. Provide fire extinguishers and wall brackets:

1. Fire extinguishers.
2. Fire extinguisher mounting brackets.

## 1.02 SUBMITTALS

- A. Submit for approval shop drawings, product data.

## 1.03 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.
- B. Standards: UL and FM listed products, NFPA 10.
- C. Regulations: ADAAG.

## **PART 2 - PRODUCTS**

### 2.01 MATERIALS

- A. Manufactures: J. L. Industries, Larsen's Manufacturing, Potter-Roemer or approved equal.
- B. Fire Extinguishers: (at locations shown on plans.)
  - 1. Type: Multipurpose dry chemical type, for Class A, B, and C.
  - 2. Size: 5 pound capacity.
- C. Cabinets:
  - 1. Mounting: Surface-mounted.

## **PART 3 - EXECUTION**

### 3.01 INSTALLATION

- A. Install fire extinguishers in all areas with wall-hung brackets at locations and heights indicated and acceptable to authorities having jurisdiction.

- B. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance. Coordinate with work of other sections.
- C. Restore damaged finishes and test for proper operation. Clean and protect work from damage.

\* END OF SECTION 10522 – FIRE EXTINGUISHERS AND WALL BASKETS

## **SECTION 10800 - TOILET AND BATH ACCESSORIES**

### **PART 1 - GENERAL**

#### 1.01 SUMMARY

- A. Provide toilet accessories and metal framed mirrors.

#### 1.02 SUBMITTALS

- A. Submit for approval samples, shop drawings, product data.

#### 1.03 QUALITY ASSURANCE

- A. Comply with governing codes and regulations. Provide products of acceptable manufacturers which have been in satisfactory use in similar service for three years. Use experienced installers. Deliver, handle, and store materials in accordance with manufacturer's instructions.
- B. Regulations: ADAAG and local accessibility requirements.

### **PART 2 - PRODUCTS**

#### 2.01 MATERIALS

- A. Manufacturers: Bobrick Washroom Equipment, or approved equal.
- B. Toilet Accessories:

1. Paper towel dispensers, B-262, "C-fold."
2. Toilet tissue dispensers, single roll, B-685.
3. Grab bars, B-6806, (1-48" L, 1-36" L).
4. Shower curtain rods, B-6047-48.
5. Shower curtains and hooks, vinyl, 204-3-70" wide.
6. Soap dishes, surface mounted.
7. Towel bars, B-674-24, 2 required.
8. Robe hooks, B-682, 2 required.

C. Mirrors and Frames:

1. Glazing: Mirror glass, 1/4 inch thick, ASTM C 1036, B-166, 18" W X 36" H.
3. Frames: Stainless steel with shelf.
6. Type: Standard wall unit.

D. Materials and Finishes:

1. Stainless Steel: AISI Type 302 or 304, No. 4 polished finish.
2. Chromium Plated Brass or Steel: ASTM B 456, Type SC 2.
3. Phenolic Faces: High-pressure melamine.
4. Baked Enamel on Steel: Factory-applied gloss white.

### **PART 3 - EXECUTION**

#### 3.01 INSTALLATION

- A. Install materials and systems in accordance with manufacturer's instructions and approved submittals. Install materials and systems in proper relation with adjacent construction and with uniform appearance. Coordinate with work of other sections.
- B. Restore damaged finishes and test for proper operation. Clean and protect work from damage.

\*\*\*\*\* END OF 10800 – TOILET AND BATH ACCESSORIES \*\*\*\*\*

\*\*\*\*\* END OF DIVISION 10 – SPECIALITIES \*\*\*\*\*